

WINSTON

| | | | |
|------------------------------|--|---------------|------------|
| Manufacturing process | Tufted | | ISO 2424 |
| Gauge | 1/8" Loop | | |
| Pilecomposition | 100% PP | | ISO 2424 |
| Primary backing | Woven PP | | ISO 2424 |
| Secondary backing | Felt | | ISO 2424 |
| Width | 400 cm | ± 1% | EN 986 |
| Pile weight | approx. 530 gr/m ² | | ISO 8543 |
| Total weight | Felt : approx. 1704 gr/m ² | ± 15% | ISO 8543 |
| Pile height | approx. 3,5 mm | | ISO 1765 |
| Total height | AB : approx. mm Felt : approx. 6,0 mm | + 15% / -10% | ISO 1765 |
| Number of knots | approx. 142.313 /m ² | + 10% / -7,5% | ISO 1763 |
| Fire classification | Felt : Efl | | EN 13501-1 |
| Light fastness | ≥ 5 | | 105-B02 |
| Wearability | ≥ 4 | | 105-X12 |
| Water fastness | ≥ 4 | | 105-E01 |
| Thermal resistance | 0,130 m ² K/W | | ISO 8302 |
| Sound insulation | 10,0 dB | | ISO 10140 |
| GUT Nr. | Felt : D9A116E2 | | |

Floorsymbols Felt



Certificates

