

**THE NEXT
GENERATION**
15 YEARS GUARANTEE*
check-floors.com

CHECK ✓
one

Standard Collection
with integrated underlay

Product information

| | |
|-------------------|--|
| Guarantee | 15 years* |
| Clicksystem | Loc-Click |
| Chamfer | bevelled edge (plank) 4V-groove (wide plank) |
| Sealing | UV varnish |
| Wear layer | 0.3 mm |
| Utilisation class | 33 (plank) 34 (wide plank) |

Technical data

| | | |
|-------------------|------------|-----------------------|
| Dimension | | 1220 x 182 x 5 mm |
| Packing unit (PU) | Plank | 10 Planks = 2.220 sqm |
| Pallet size | | 44 PU = 97.70 sqm |
| Dimension | | 1220 x 228 x 5 mm |
| Packing unit (PU) | Wide Plank | 8 Planks = 2.225 sqm |
| Pallet size | | 39 PU = 86.79 sqm |

Test results

| | | |
|-----------------------------|------------------------|---|
| Lightfast | ISO 105-B02 | 6 |
| Dimensional stability | ISO 23999 | ✓ |
| Fire behavior | EN 13501-1 | Bfl, s1 |
| Straightness and squareness | ISO 24342 | 0.03 mm / 0.04 mm |
| Resistance to staining | EN ISO 26987 | ✓ |
| Residual indentation | ISO 24343 | 0.02 mm |
| Slip resistance | EN 13893 | DS |
| Anti-Slip property | DIN 51130 | R10 |
| Thermal Resistance | EN12667 | 0.061 m ² K/W |
| Underfloor heating | EN12667 | Suitable for hot water, max. 27 degrees |
| Formaldehyde class | EN 717-1 | E1 |
| Chair castor suitability | ISO 4918 | no damage |
| Impact sound reduction | ISO 10140-1; ISO 717-2 | 19 dB |

* according to guarantee conditions

All specified values are standard values.
Production-related fluctuations can not be ruled out.


KOCZWARA
gemeinsam wachsen!