

Tavares

Tuft gauge	1/10 cut pile		ISO 2424
Pilecomposition	100% PP		ISO 2424
Primary Backing	Woven		ISO 2424
Secondary backing	AB, Felt		ISO 2424
Width	400 cm, 500 cm	± 1%	EN 984
Pile Weight	1350 gr/m ²		ISO 8543
Total weight	AB : 2160 gr/m ² Felt : 2210 gr/m ²	± 15%	ISO 8543
Pile height	7,5 mm	± 2 mm	ISO 1766
Total Height	AB : 9,5 mm Felt : 10,5 mm		ISO 1765
Number of knots	183.524/m ²	-7.5% .+10%	ISO 1763
Fire Classification	Cfl-s1	EN 13501-1	
Use Area	Heavy domestic use (23)		EN 1307
GUT Nr.	B01B8652 GUT		www.pro-dis.info
Sound Insulation	Ca. 25 dB		ISO 10140
Thermal resistance	0,098 M ² KW		ISO 8302
Light fastness	≥ 5		105-B02
Wearebility	≥ 4		105-X12
Water fastness	≥ 4		105-E01

Floorsymbols



Certificates



2017
 Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP C-026AU015
 Reaction to fire:
 Cfl-s1
 Slip resistance: DS
 AB
 Resilient floor
 covering to be
 used within a
 building



2017
 Condor Carpets
 Euroweg 3
 8061 SB Hasselt
 EN1307
 DOP C-026FU015
 Reaction to fire:
 Cfl-s1
 Slip resistance: DS
 Felt
 Resilient floor
 covering to be
 used within a
 building



Intenza
 the ultimate in soft carpets

