

PM FLEUVE

REPOSE COLLECTION

**HIGH
PERFORMANCE
COLLECTION**

CONSTRUCTION STRUCTURE STRUKTUR STRUCTUUR	Tufting 1/10" saxony Tufté 1/10" saxony Getuftet 1/10" saxony Getuft 1/10" saxony	EN 985 A: intensive use
PILE MATERIAL COMPOSITION DU VELOURS POLMATERIAL POOLMATERIAAL	100% PA 6	EN 1963 A: intensive use
PRIMARY BACKING SUPPORT TRÄGERMATERIAL TUFTDOEK	Non woven PES Non tissé Vlies Felt	ISO 6356 < 2 kV
SECONDARY BACKING DOSSIER RÜCKEN TAPIJTRUG	Action back	ISO 140-8 24 dB ΔLw
PILE WEIGHT POIDS DU VELOURS POLEINSATZGEWICHT POOLGEWICHT	± 900 gr/m ²	ISO 354 0,20 aw
TOTAL WEIGHT POIDS TOTAL GESAMTGEWICHT TOTAAL GEWICHT	± 1.875 gr/m ²	ISO 8302 0,08 m ² K/W
PILE HEIGHT EPAISSEUR DU VELOURS POLHÖHE POOLHOOGTE	± 4,2 mm	ISO 105-B02 ≥ 5-6
TOTAL HEIGHT EPAISSEUR TOTALE GESAMTHÖHE TOTAAL HOOGTE	± 7,0 mm	EN ISO 105-E01 ≥ 4-5
TUFT DENSITY NOMBRE DE POINTS NOPPENZAHL AANTAL PUNTEN	± 173.000/m ²	EN ISO 105-X12 ≥ 4
PILE DENSITY DENSITÉ DU VELOURS POLROHDICHTE POOLDICHTHEID	± 0,143 g/cm ³	EN 13501-1 Bfl-s1 if glued
CLASSIFICATION CLASSEMENT KLASSIFIKATION CLASSIFICATIE	EN 1307 32 - LC2	EN ISO 3018 ± 400 cm
DESIGN REPEAT CM RACCORD CM RAPPORT CM DESSINRAPPORT CM	±99(W) x ± 96 (H)	
PRODIS / GUT	1721C645	
UPEC	U3 P3 E1 C0 Certification CSTB: 10/276	

itc

QB UPEC
moquettes touffelées et tissées en lés
<http://evaluation.cstb.fr>



EN 14041
CE
25
ITC CO BV Kanegemstraat 15 - BE 8700 Tielt
DOP: 1011#IE0ABV
Textile Floor Covering EN1307 Notified Body 2401
my.itc-carpets.com

PM FLEUVE

REPOSE COLLECTION


ALL-PURPOSE DESIGN



95




44



18



98



39



64



52



ITC CO BV - Kanegemstraat 15 - B-8700 Tielt - Belgium - hello@itc-carpets.com - itc-carpets.com

12/25 All rights reserved to alter technical specification - Sous réserve de modifications techniques - Unter Vorbehalt von technischen Änderungen - Onder voorbehoud van wijzingen van de technische specificaties.